MULTI CHANNEL AMPLIFIER

The Apart SIXPACK is a multi channel amplifier that consists of 6 stereo amplifiers. This makes the SIXPACK very suited for matrix systems and multi-room audio and zoning systems.

Each amplifier has a power handling of 2 x 80 Watts in 4 Ohm. Every amplifier is equipped with balance and tone control and has a remote power on system.
The volume of each amplifier can be controlled over distance via an up - down contact.

The modular aspect, together with the build-in limiters and extended protection circuit, contributes to the reliability of the SIXPACK and allows easy servicing. On top of that, the modular amplifiers make your system design very flexible.

The SIXPACK comes with short AC linking cables so that only one power plug is needed.

TECHNICAL SPECIFICATIONS

Input Line in	RCA Cinch unbalanced, 775 mV, 20 kOhm
Output Power (RMS Program)	8 Ohm: 12 x 60 watt / 12 x 80 watt Max
	4 Ohm: 12 x 80 watt / 12 x 100 watt Max
Frequency Response	20 Hz - 30 kHz
Tone control	Bass 70 Hz +/- 10 dB, Treble 10 kHz +/- 10 dB
Limiter	Dynamic-slow @ -3 dB, defeatable
Distortion	<0.02%
Remote volume	Euroblock; via up - down contact
Remote power on selector	On/off switch on front - by audio signal - by 5-24Vdc
Loudness	Via push button
Power Supply	230V
Dimensions (H x W x D)	179 x 483 x 360 mm
Weight	24.65 Kg